# SOFSTOP COLUMN PADDING

2” and 3” Polyurethane Filler **95-100 ILD (Meets Cal. 117)
2” Bonded Foam Filler 6 lb. Density
2” Neoprene Foam Filler (Meets ASTM-E84 Class “A”) 6 lb. Density.
1-1/2” Polyurethane Filler **95-100 ILD (Meets Cal. 117)
1-1/4” Polyethylene Filler (Closed Cell)
**ILD – Indentation Load Deflection
*Additional foam options available

SofStop u-shaped column padding will be constructed of (Filler – see descriptions above) cemented to 7/16 oriented strand board and covered with a Fire Retardant 14oz. PSY vinyl laminate with a polyester scrim reinforcement or covered with a 16oz or 18oz PSY premium coated heavy duty vinyl. All vinyls have high UV, mildew and rot resistance and meet the following fire retardant specifications (Fire Retardant to pass California State Fire Marshall’s Test NFPA-701 and ASTM-E84 Class A). The vinyl covering shall be folded and stapled securely to 7/16” oriented strand board.

A 1” nailing margin shall be provided top and bottom for securing panels to the wall with appropriate anchors supplied by the installer. For a standard 2’-0 wide pad, three anchors on each nailing margin shall be used. Trim washers can be used at each fastener location to improve appearance. Likewise, an aluminum strip can be used to cover the entire nailing margin, but is not necessary. Should Z-clips be used, foam height remains the same as a pad with two nailing lips; however, one nailing lip or both nailing lips can be eliminated. Custom height z-clip padding will be made per project specifications.

SofStop padding is available in any height from 1’-0 to 10’-0.

Vinyl laminated polyester covering is available in 17 colors: Maroon, Red, Rich Red, Orange, Yellow, Light Gold, Kelly Green, Forest Green, Marine Blue, *Teal, Royal Blue, Navy Blue, Dark Blue, Purple, Beige, Gray, Black, and White.

*Not available on a Class “A” pad

Custom cutouts in panels shall be made in the field to ensure proper fit.